

# AQSync Air Quality Monitoring Station:

## Detailed Specifications

Instrument/Sensor Specifications (per manufacturer)	
<b>Ozone (O<sub>3</sub>)</b> <b>Measurement Method:</b> UV Absorbance at 254 nm <b>Instrument:</b> 2B Technologies Model 108-L (FEM) <b>Linear Range:</b> 0-100,000 ppb <b>Precision:</b> 1.5 ppb or 2% of reading for 10-s avg <b>Accuracy:</b> 1.5 ppb or 2% of reading <b>Response Time:</b> 4 s for 2-s avg, 20 s for 10-s avg	<b>Nitrogen Dioxide (NO<sub>2</sub>)</b> <b>Measurement Method:</b> Direct Absorbance at 405 nm <b>Instrument:</b> Based on 2B Tech Model 405 nm NO <sub>2</sub> /NO/NO <sub>x</sub> Monitor (FEM approval pending) <b>Linear Range:</b> 0-10,000 ppb <b>Precision:</b> 0.5 ppb <b>Accuracy:</b> 2 ppb or 2% of reading <b>Response Time:</b> 20 s
<b>Nitric Oxide (NO)</b> <b>Measurement Method:</b> Oxidation to NO <sub>2</sub> with O <sub>3</sub> followed by Absorbance of NO <sub>2</sub> at 405 nm <b>Instrument:</b> 2B Tech Model 405 nm NO <sub>2</sub> /NO/NO <sub>x</sub> Monitor <b>Linear Range:</b> 0-2,000 ppb <b>Precision:</b> 0.5 ppb <b>Accuracy:</b> 2 ppb or 2% of reading <b>Response Time:</b> 20 s	<b>Particulate Matter (PM<sub>1</sub>, PM<sub>2.5</sub>, PM<sub>10</sub>)</b> <b>Measurement Method:</b> Optical Particle Counter, right angle light scatter detection with sheath flow and heated inlet <b>Instrument:</b> Met One Instruments Model 83214 <b>Range:</b> 0-320,000 particles per liter <b>Minimum Particle Size:</b> 0.3 µm <b>Accuracy:</b> 10% <b>Response Time:</b> minimum 1 s
<b>Carbon Dioxide (CO<sub>2</sub>)</b> <b>Measurement Method:</b> Non Dispersive Infrared (NDIR) Absorbance with Auto-Zeroing <b>Instrument:</b> PP Systems CO <sub>2</sub> Gas Analyzer, Model SBA-5 <b>Linear Range:</b> 0-1,000 ppm <b>Precision:</b> 1 ppm <b>Accuracy:</b> 5 ppm <b>Response Time:</b> 10 s	<b>Carbon Monoxide (CO)</b> <b>Measurement Method:</b> Amperometry <b>Linear Range:</b> 0-50 ppm <b>Sensor:</b> Alphasense CO-A4 <b>Precision:</b> 0.02 ppm <b>Accuracy:</b> 0.1 ppm <b>Response Time:</b> 20 s
<b>Total VOCs</b> <b>Measurement Method:</b> Photoionization Detector <b>Sensor:</b> ION Science Mini-PID2 HS <b>Measurement Range:</b> 0 to 3 ppm <b>Sensitivity:</b> > 600 mV per ppm <b>Minimum Detection Limit:</b> 0.5 ppb <b>Response Time:</b> < 12 s	

\*Option for SO<sub>2</sub> sensor; contact 2B Tech for information.

## System Specifications

<b>Weight</b>	54.5 lb, 24.8 kg (varies with modules chosen)
<b>Size</b>	25.5 H x 25.5 W x 10.3 D in (65 x 65 x 26.2 cm); height with weather station is 49 in (124.5 cm)
<b>Power</b>	35 watt (53 watt max during warmup) (varies with modules chosen)
<b>Data Transmission</b>	Cellular or WiFi to the Cloud; Ethernet option
<b>Sample Flow Rate</b>	~4 L/min (varies with modules chosen)